



800-558-2240 (Samples)  
800-366-2689 ext. 2709 (Tarkett Commercial Technical Assistance)  
FAX: 713-869-5271 (Tarkett Commercial Technical Assistance)

Technical Assistance E Mail: [TarTech@Tarkett.com](mailto:TarTech@Tarkett.com)

## **SECTION 09.65.19.00 - VINYL COMPOSITION TILE**

- A. Type: Tarkett, Vinyl Composition Tile, ASTM F 1066, non-asbestos formulated; 12 inch by 12 inch, 1/8 [3/32] inch gauge; minimum 1.0 CRF per ASTM E 648; maximum smoke density of 450 per ASTM E 662; static load limit of 150 psi or higher; minimum slip resistance rating for floors of > 0.60.
  - 1. Manufacturer: Tarkett Commercial, Telephone 800-558-2240 (samples) and 800-366-2689 ext. 2709 (Tarkett Commercial Technical Assistance); Fax 713-869-5271 (Tarkett Commercial Technical Assistance). E-mail Technical Assistance: [TarTech@Tarkett.com](mailto:TarTech@Tarkett.com)
    - a. Standard Pattern Expressions (55 colors).
    - b. Premium Pattern Stoneworks (12 colors).
    - c. Premium Pattern Details (7 colors)
    - d. Premium Pattern Feature Strip (7 colors) [1/4", 1/2", 1", 2", 4", 6" by 24" sizes available]
    - e. Premium Pattern True-Step (2 colors), slip resistance rating of 0.8.