



800-558-2240 (Samples)  
800-366-2689 ext. 2709 (Tarkett Commercial Technical Assistance)  
FAX: 713-869-5271 (Tarkett Commercial Technical Assistance)

Technical Assistance E Mail: [AzTech@Tarkett.com](mailto:AzTech@Tarkett.com)

## SECTION 09.65.19.00 - VINYL COMPOSITION TILE

- A. Type: Azrock Vinyl Composition Tile, ASTM F 1066, Class 1 or 2, non-asbestos formulated; 12 inch by 12 inch, 1/8 [3/32] inch gauge; minimum 1.0 CRF per ASTM E 648; maximum smoke density of 450 per ASTM E 662; static load limit of 125 psi or higher; minimum slip resistance rating for floors of > 0.60.
1. Manufacturer: Azrock by Tarkett Commercial, Telephone 800-558-2240 (samples) and 800-366-2689 ext. 2709 (Tarkett Commercial Technical Assistance); Fax 713-869-5271 (Tarkett Commercial Technical Assistance). E-mail Technical Assistance: [AzTech@Tarkett.com](mailto:AzTech@Tarkett.com)
    - a. Standard Pattern, Class 2, Cortina Colors (27 colors).
    - b. Standard Pattern, Class 2, Cortina Classics (38 colors).
    - c. Premium Pattern, Class 1, Solids (14 colors)
    - d. Premium Pattern, Class 1, Feature Strip (14 colors) [1/4", 1/2", 1", 2", 4", 6" by 24" sizes available]
    - e. Premium Pattern, Class 2, Granite (10 colors).
    - f. Premium Pattern, Class 2, Granite Slip Resistant (13 colors); slip resistance rating of 0.8.

**Specifier Note:** Cortina Standard Patterns are available with StoneGlow, photo luminescent chips (dispersed evenly across the tiles which will illuminate a pathway to help people exit safely in emergency situations) by special order, subject to minimum order size and production schedule.

- 
- 
- 
- 
- 
- 
- g. Premium Option, Class 2, StoneGlow